


VCA3-203, 205 14 Pin Dip Crystal Oscillators


Featuring:

- ± 20 ppm stability including aging
- -40 to 85°C operating temperature
- 3.3 or 5.0 VDC
- Enable/disable option



Frequency Range	1.544 MHz to 60 MHz
Package	0.8" x 0.5" x 0.4" max 4 pin thru-hole
Voltage Options/ Load Drives	203 = +3.3 Vdc $\pm 10\%$ 15 pF 205 = +5.0 Vdc $\pm 10\%$ 15 pF
Electrical	Tristate 55/45 Symmetry
Enable/Disable	Logic 1 or NC = Enable (Oscillation) Logic 0 or GND = Disable (High Impedance)
Stability	± 20 PPM -40 to 85°C, for 10 years all parameters*
Start-Up	10 ms Maximum
Load	HCMOS/TTL
Current	50 mA Maximum
Standard Packaging	Anti Static Tubes
Standard Frequencies	19.44 MHz, 24.704 MHz, 32 MHz, 32.768 MHz, 34.368 MHz, 44.736 MHz
Typical P/N	VCA3-203-19M44 VCA3 = 0.8" x 0.5" x 0.4" max 4 pin thru-hole 203 = +3.3 Vdc $\pm 10\%$, ± 20 PPM -40°C to +85°C for 10 years, all parameters

* NOTE: All parameters include aging, initial accuracy, thermal stability, load, solder reflow, vibration



mm
in